






















FMS 300 TECHNICAL INFORMATION

Shape		Dimensions (in.)	min Ø (in.)	Rolls
	1	8x1	79	A,D
	2	8x3/4	79	A,D
	3	8x1	1800	A,D
	4	8x3/4	2800	A,D
	5	8x1-1/8	1800	A,D
	6	10x2-3/8	79	A
	7	18x2-3/4	1000	A
	8	6	2500	A
	9	Ø170	1700	B
	10	Ø12-3/4x2/5	4200	B
	11	-	-	B
	12	12x4x5/16	*	B
	13	-	-	-
	14	8-5/8x1/2	*	B
	15	19-5/8	79	B
	16	19-5/8	79	B
	17	10-1/4	10000	C,B
	18	19-5/8	79	B
	19	12	13000	C,B
	20	12-9/16	2500	B
	21	8-5/8	9600	C,B
Section Modulus	cm³	42-3/4		
Motor Power	H.P.	86		
Roll Diameter	in.	Ø29.133		
Shaft Diameter	in.	Ø11.811 / Ø11.023		
Bending Speed	in./min	23		
Weight	lb.	58,202		
WxLxH	in.	132x171x89		

A: Standard Rolls | B: Special Rolls | C: Pulling Device | D: Special rolls for serial productions | E: Angle Device | F: Stretching Device

*Smallest bending diameter depends on grade of deformation that can be accepted.